

PRODUCT-DETAILS

# 316BC6W

## Ind. P&S#316BC6W



### General Information

Extended Product Type	316BC6W
Product ID	2CMA102175R1000
EAN	7392696021753
Catalog Description	Ind. P&S#316BC6W
Long Description	4x16A / IP 67 - Connector Clock Position Of Grounding Contact 6 hour Color code Red

### Ordering

EAN	7392696021753
Country of Origin	Turkey (TR)
Minimum Order Quantity	10 piece

### Dimensions

Product Net Width	89 mm
Product Net Height	89 mm
Product Net Length	143 mm
Product Net Depth / Length	143 mm
Product Net Weight	0.248 kg

---

**Container Information**


---

Package Level 1 Width	150 mm
Package Level 1 Depth / Length	280 mm
Package Level 1 Height	225 mm
Package Level 1 Gross Weight	2.663 kg
Package Level 1 EAN	7392696036559
Package Level 1 Units	box 10 piece

---



---

**Technical UL/CSA**


---

Ampere Rating UL/CSA	16 A
----------------------	------

---



---

**Certificates and Declarations (Document Number)**


---

Declaration of Conformity - CE	2CMC700005D0001
Declaration	2CMC700005D0001
Environmental Information	2CMC000072M0000
RoHS Information	2CMC700005D0001
REACH Declaration	2CMC700005D0001

---



---

**Additional Information**


---

Additional Information	3P+E
Ambient Temperature	-40 ... 70 °C
Cable Cross-Section	1 ... 2.5 mm <sup>2</sup>
Cable Entry Position	Anti-kink sleeve
Color	Red
Connection Type	Screw
Degree of Protection	IP67
Frequency (f)	50 Hz 60 Hz
Function	Connector
Housing Material	Plastic (PA)
Invoice Description	Ind. P&S#316BC6W
Number of Poles	4
Order Multiple	10 piece
Product Main Type	BC
Product Name	Connector
Protection Type	Watertight
Rated Current ( $I_n$ )	16 A
Rated Voltage ( $U_r$ )	380 ... 415 V
Replacement Product ID (NEW)	2CMA193276R1000

---

Standards	IEC 60309-1, -2
Suitable for Product Class	IEC Industrial Plugs and Sockets
Instructions and Manuals	2CMC700014C0016
RAL Number	RAL 7012 - Basalt Grey

---

## Classifications

---

eClass	27440509
UNSPSC	39120000

---

---

## Categories

---

Low Voltage Products and Systems → Industrial Plugs and Sockets → Basic & Safe

